


ALC-Tech (M) Sdn Bhd (610609-M)

30-1 Jalan 6/62A Bandar Menjalara, 52200, Kepong, Kuala Lumpur, Malaysia.

TEL: (603) 62801650 FAX: (603) 62804595

url: www.alcglobal.com email: sales-KL@alcglobal.com

R-200



The R-200 delivers industrial printer capacity and durability in a cost-effective package. Large ribbons are often required for the volume printing tasks in an industrial environment. The R-200 loads standard 360-meter ribbons that are suitable for industrial uses. This printer comes in two models that are different only in the types of ribbons used. The R-200 accepts ribbons with inside coating, while the R-200K accepts ribbons with outside coating. Direct thermal and thermal transfer printing methods provide resolution of 203dpi. The 16-bit RISC CPU and 512KB of memory allow print speeds of up to 4ips. The R-200 model printer offers industrial performance for an entry-level cost.

Specifications

> Printing method	Direct thermal & Thermal Transfer
> Printing resolution	203 dpi
> Printing Speed	2 ~ 4
> Printing Length	0.4 ~ 8
> Printing Width	Max 4.1
> Display	LED indicators x 3
> Memory	512KB/ 512KB
> CPU Type	16 bit
> Media Sensor	Reflective (Movable)
> Ribbon	Wax, Wax/Resin, Resin (inside coating) , Ribbon width – 2", 4, Ribbon roll – max 2.67" (OD 68 mm) Ribbon length – re-sin 300 m , wax 360 m (OD 68 mm), Core size - ID 1" core (25 mm)
> Weight	9.3 lbs (4.2 kegs)
> Operation interface	Button x 3
> Comm. interface	Parallel, RS-232
> Power Source	External Power Adapter
> Agency listing	CE, UL, CUL, FCC class A, CCC
> Dimensions	W 314 x H 231 x L 218 mm
> 2D barcodes	Maxicode, PDF-417, Data Matrix (ECC-200 only)
> Graphics	PCX bit map, GDI graphics
> Fonts	Int'l character sets standard , 5 alpha-numeric fonts from .049"~.23"H (1.25mm ~ 6.0mm) Fonts are expandable to 24x24, 4 direction 0°~270° rotation, Soft fonts are downloadable
> Software	ARGOX PPLB Language Windows Driver (Win 98/2000/NT/XP) Label editing software – ArgoBar, Printer Utility
> Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper and fabric label Max width 4.3" (110 mm), Min width 1" (15 mm) Thickness .0025"~. 01" (.0635mm ~. 254mm) Max roll capacity 6" (OD 152 mm), Core size 1"~1.5" (25mm ~ 37mm) (Core sized 3" ID can be applied by installing with extra media core adapter)
> Mechanism request	Built-in Tear off bar, front-open cover, clear window, fan fold paper back cover, face-in ribbon run way.
> Op. environment	40° F ~ 100° F (4°C~38°C) 10~90% non condensing
> Optional items	Cutter, Dispenser kit, Real time clock card, ArgoNet print server, Asian font card.