

X-3000+ Printer

The X-3000+ printer is ideal for applications that require small labels or textile media. Its standard 300-dpi print head ensures superior printing quality for first-class characters, graphics and barcodes. The X-3000+ 's combination of features and power provides greater productivity and cost advantage to the user.

Industrial-strength construction and proven reliability ensure that the X-3000+ will withstand the most demanding environments. Built-in 2 MB of memory and a 32-bit microprocessor enable the printer to rapidly format labels and achieve constant print speeds of up to 6 inches per second.

Standard features are 4.25-inch (108mm) maximum printing width, standalone operation, auto label calibration, auto label counting, and an anti-jam media path. Other features include the resident typographic font set, international character sets, and support for linear and 2-D symbology.

Hardware features include an RS-232 serial port, a Centronics port, a PS2 keyboard wedge, a 2 1/2" LCD display, a clear door panel, and a switching power supply.

The X-3000+ is also bundled with free Windows 95/98/2000/NT drivers and WYSIWYG software(ArgoBar) for instant operation.



Specification

Printing method	Direct thermal & Thermal transfer	
Printing resolution	300 dpi (12 dots/mm)	
Max printing speed	2~6 ips (51~152 mm/s)	
Max printing length	0.5"~30" (13~762 mm)	
Max printing width	1.0"~4.25" (25~108mm)	
Fonts	Int'l character sets standard from .049"~ .23"H (1.25mm~6.0mm) 4 direction 0°~270° rotation	5 alpha-numeric fonts All fonts are expandable up to 24 x 24 Soft fonts are downloadable
Barcodes	Code 39, Extended Code 39 Code 128(Subset A,B,C) Codabar EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25	Code 93, Code 128 UCC Interleave 2 of 5, EAN-8 2&5 add on,
2D Barcodes	Maxicode, PDF-417	
Graphic	PCX bit map, GDI graphics	
Memory	2MB DRAM, 1MB Flash ROM	
Interfaces	RS-232 serial, Centronics parallel	
Media	Roll-feed, die-cut, continuous, fan-fold, tags, Ticket in plain paper or thermal paper Min width 1.0" (25 mm) Min length 0.4" (10 mm) Max roll capacity 8" (203mm) OD	Max width 4.3" (110 mm) Max length 0.4" (10 mm) Thickness .0025"~.01(.0635mm~.254mm) Core size 1.5"~3.0" (38mm~76mm) ID
Ribbon	Wax, Wax/Resin, Resin Ribbon roll-Max OD 3" (76mm) Ribbon width 1.3", 2.5", 3.3, 4.3" (33mm, 64mm, 84mm, 109mm)	Ribbon length- Max 1182" (360m) Code size- ID 1" core (25mm)
Compact size	W 9.8" x L 16.0" x H 10.2" (W 250x L 410 x H 260 mm)	
Weight	24.6 lbs (11 kgs)	
Power source	110/220 VAC ± 10%, 50/60 Hz	
Agency listing	CE, UL, CUL, FCC class A	
Operation environment	40°F ~ 100°F (4°C~38°C)	10~90% non condensing
Software	ARGOX PPLA & PPLB Language Label editing software – ArgoBar	Windows Driver (Win 31/95/98/NT) CODESOFT 4 XLT PLUS
Optional items	Cutter, Dispenser kit, Real time clock External 8"OD media stacker, ArgoNet print server	Extension SRAM memory, Extension flash memory, Standalone KDU - ArgoKee,