

HONEYWELL GEN8 DB

007643
Issue 2


Miniature Decoder Board

Honeywell next generation, miniature decoder board is packed with powerful processing and performance that unleashes the Honeywell Smart Adaptus™ 8.0 platform through its dual core processors and 4x memory speed.

The Honeywell Gen8 DB Decoder Board is the next generation platform that follows the successful Gen7 DB and MINI DB Decoder Boards. With its ultra-powerful processor, combined with Honeywell's comprehensive barcode symbology support, the GEN8 DB delivers superior decoding performance for all barcode types and beyond, including OCR applications.

Through its 1.2 GHz dual processor and 4x memory speed, the GEN8 DB enables near-term and future application flexibility over the total cost of ownership, further providing flexibility tailored to changing development needs. It is also flash-upgradable, catering to maintenance needs, continuous innovation and support.

Designed to simplify complex integrations and streamline OEM configurations, the GEN8 DB is equipped with MIPI interface with optional TTL or USB interface support. Customers may choose either a TTL serial or USB interface for board-to-board, snap-on installation to the customer's main board which is then secured using additional hold-down screws. This "cable-less" solution eliminates the need for an additional flex cable and connector while providing a more compact footprint. This product is also built on the same form factor footprint as the GEN7 DB and MINI DB, providing drop-in mechanical fit, allowing customers to expect frictionless migration from current designs to the GEN8 DB platform.



Honeywell GEN8 DB, front and back views

FEATURES AND BENEFITS



- Powerful 1.2 GHz dual processor and 4x memory enable future proofing of your end applications to maximize your total cost of ownership



- Packaged in a compact and sleek 20 mm x 14 mm [0.79 in x 0.55 in] form factor that provides design and real estate flexibility



- MIPI interface reduces development costs and simplifies integration



- Frictionless migration at your own ease and convenience from GEN7 DB to GEN8 DB



- Supports beyond barcodes functionalities such as OCR and Swiftdecoder microservices to implement value-added custom features such as Honeywell EasyDL™

Honeywell

GEN8 DB MINIATURE DECODER BOARD Technical Specifications

TABLE 1. MECHANICAL

CHARACTERISTIC	PARAMETER
Dimensions (L x W x H)	20 mm × 14 mm × 4,8 mm [0.79 in × 0.55 in × 0.19 in]
Interface: input output	34-pin connector for scan engine MIPI interface board-to-board connector with RS TTL and USB HS (480 Mbit/s) available

TABLE 2. PERFORMANCE

CHARACTERISTIC	PARAMETER		
	GEN8 DB + N6803MR SCAN ENGINE	GEN8 DB + N6803FR SCAN ENGINE (RED AIMER)	GEN8 DB + N6803FR SCAN ENGINE (GREEN AIMER)
Input voltage	3.15 V to 3.45 V		3.3 V
Operating current at 3.3 V: RS mode USB full speed USB high speed INRUSH (maximum)	475 mA (RMS, exposure time: 12.5 ms) 490 mA (RMS, exposure time: 12.5 ms) 490 mA (RMS, exposure time: 12.5 ms) 700 mA	417 mA (RMS, exposure time: 9 ms) 422 mA (RMS, exposure time: 9 ms) 432 mA (RMS, exposure time: 9 ms) 650 mA	584 mA (RMS, exposure time: 15 ms) 603 mA (RMS, exposure time: 15 ms) 610 mA (RMS, exposure time: 15 ms) 650 mA
Idle current at 3.3 V (scan engine powered): RS mode USB full speed USB high speed	175 mA (RMS) 185 mA (RMS) 190 mA (RMS)	148 mA (RMS) 155 mA (RMS) 165 mA (RMS)	158 mA (RMS) 166 mA (RMS) 175 mA (RMS)
Idle current at 3.3 V (scan engine not powered): RS mode USB full speed USB high speed	125 mA 130 mA 135 mA	125 mA 130 mA 138 mA	125 mA 130 mA 138 mA
Standby/suspend: RS mode USB full speed USB high speed	4.5 mA (RMS) 3.8 mA (RMS) 4.2 mA (RMS)	8 mA (RMS) 8.1 mA (RMS) 8.3 mA (RMS)	4 mA (RMS) 3 mA (RMS) 3 mA (RMS)
Working mode	<ul style="list-style-type: none"> operation (scanning/decoding) idle standby (RS)/suspend (USB) power off 		
Indicators	beeper and green LED signals available on the output connector		
Supported scan engines	EX30, N5703, N6703, N6803FR, and N6803MR		
Supported software	EZConfig, HSM USB Serial Driver		
MTBF*	1,741,553 hours		
Warranty	15-month limited warranty; the warranty period starts at date of shipment from Honeywell to customer		

* Based on MIL-HDBK-217F (released December 1, 1991). The calculation is based on the part count method for the Ground Benign (GB) environmental conditions.

Figure 1. Honeywell GEN8 DB with the N6803MR Scan Engine




Figure 2. Honeywell GEN8 DB with the N6803FR Scan Engine (red aimer)




Figure 3. Honeywell GEN8 DB with the N6803FR Scan Engine (green aimer)



GEN8 DB MINIATURE DECODER BOARD Technical Specifications

TABLE 3. DECODER BOARD COMPARISON				
CHARACTERISTIC	GEN8 DB	GEN7 DB	MINI DB	GEN6 DB
Scan engine compatibility	EX30, N5703, N6703, N6803MR/FR	Extended FlexRange EX30, N660X Series, N670X Series, N3601	N560X Series, N660X Series	
Dimensions	20 mm × 14 mm [0.79 in × 0.55 in]			39,8 mm × 19,1 mm [1.6 in × 0.75 in]
Input voltage	3.3 V			3.3 V, 5 V
Processor	Ingenic, 1.2 GHz	Ingenic, 1 GHz	IMX25, 400 MHz	IMX25, 400MHz
Connection	board-to-board, board-to-ZIF			micro USB, board-to-ZIF
Interface	TTL, USB			TTL, USB 1.1, USB 2.0

TABLE 4. ENVIRONMENTAL	
CHARACTERISTIC	PARAMETER
Temperature ranges: operating storage	-30°C to 60°C [-22°F to 140°F] -40°C to 70°C [-40°F to 158°F]
Humidity	95 %RH at 60°C [140°F]
Shock	18 shocks at 3500 G/0.4 ms
Compliance and regulatory requirements	EMC Class B, FCC Class B
Safety	<ul style="list-style-type: none"> • CB Scheme: IEC 62368-1: 2018 • UL/C-UL (Recognized Component) • UL 62368-1 Third Edition • CSA C22.2 NO. 62368-1, 3rd Edition

TABLE 5. SYMBOLOGIES
LINEAR
Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar
2D STACKED
Codablock A, Codablock F, PDF417, MicroPDF417
2D MATRIX
Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin), Grid Matrix, Dot Code
POSTAL
Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet

ADDITIONAL INFORMATION

- Integration Manual is available upon request; contact your Honeywell representative
- For a listing of common compliance approvals and certifications, visit our [website](#).

NOTICE

MISUSE OF DOCUMENTATION

- The information presented in this datasheet is for reference only. Do not use this document as a product installation guide
- An installation manual is available by request on our [website](#). Please contact your Honeywell sales representative

For more information

automation.honeywell.com

Honeywell Industrial Automation

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

For a complete listing of all compliance approvals and certifications, please visit www.honeywell.com/PSScompliance

For a complete listing of all supported barcode symbologies, please visit www.honeywell.com/PSS-symbologies

SwiftDecoder™ and EasyDL™ are trademarks or registered trademarks of Honeywell International Inc. in the United States and other countries.

SwiftDecoder™ decoding software licensed by Hand Held Products, Inc.; For patent information, see www.hmpats.com