

MT-6621

6.5 inch**Rugged Handheld**

FEATURES

- Support for Windows 11/10 system
- Equipped with front 5 million and rear 8 million pixel auto focus camera
- Support 4G all network communication, Dual-band WiFi, Bluetooth and other communication modes
- Removable 7.4V 4000mAh high-voltage high-capacity battery, supports 45W Type-C PD3.0 fast charging
- Support GPS, Glonass, more accurate positioning
- Support NFC and the optional 2D module , to meet the application needs of multiple industries
- IP67 high protection level, in accordance with MIL-STD-810H

MT-6621



Specifications



Item	MT-6621
Product Form	6.5 inch Rugged Handheld
Material	ABS+PC+Metal
Dimension	183.1*88.6*24.1mm
Weight	470g
Product Color	Black
CPU	Intel JASPER LAKE N5100
GPU	Intel® UHD Graphics 620
Memory	RAM 8GB LPDDR4 ROM 128GB EMMC
Operating System	windows 10 (IOT), optional windows 11 (IOT)
Display	Type: IPS Size: 6.5 inch full laminated TFT color full screen,Dropnotch 20:9 Resolution: 720*1600 Brightness: 500cd/cm ²
Touch Pannel	5 points Capacitive, G+FF, Corning Gorilla Glass, Hardness 6H or higher, scratch-resistant.
Camera	Front 5M Rear 8M, autofocus with flash
Buttons	Power *1 Volume Adjustment Key (+) *1 Volume Adjustment Key (-) *1 Bar code scanning (left and right)*2
Speaker	Embedded 1Ω/1W speaker x 1 95dB@0.1m
Microphone	single microphone
Senssors	G_sensor *1
Battery	External polymer lithium ion battery 7.4V/4000mAh About 6 hours (50% volume sounds, 50% screen brightness, 1080P HD video display by default)
Wi-Fi	Wi-Fi 802.11(a/b/g/n/ac) Dual frequency 2.4G+5.8G WIFI
BT	BT5.0 (BLE) class1 transmission distance: greater than 10m
NFC	Support
2G/3G/4G	750VE LTE FDD: B1/B3/B7/B8/B20 LTE TDD: B40 WCDMA: B1/B5/B8 GSM: 900/1800 China (Unicom, Telecom, Mobile) Europe, Middle East, Africa, Taiwan, Japan Optional: 750-VA LTE-FDD: B2/4/5/12/13/17/18/25/26 LTE-TOD:B41 WCDMA: B2/4/5 CDMA&EVDO: BC0/BC1 GSM: 850/1900 750-VSA, LTE-FDD: B2/4/5/7/8/28 LTE-TOD:B40 WCDMA: B2/5/8 GSM:850/900/1900

MT-6621



Specifications



Item	MT-6621
GPS	GPS+GLONASS
I/O Interface	TYPE-C 2.0*1 OTG (Data transmission) Standard USB-A port/Data Transfer (3.0) TF card *1, Max: 512GB Nano-SIM * 1 Pogo Pin (Suitable docking charger DC61J)
Adapter	Input 100-240V AC 0.5A 50/60Hz Chinese standard CCC certification PD3.0 45W
USB cable	C to C
Rugged Features	Drop test height:1.5m Composite wood floor working (Power-on state) Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing
Certification	IP67 IP6X dust proof: dust cannot enter the object and the entire diameter cannot exceed the gap of the shell IPX7 waterproof: spraying water on the shell from any direction will not cause harmful effects CE FCC CCC MIL-STD-810H China Energy Conservation Certification Battery: UN38.3, MSDS, IEC62133
Data Collection	2D Barcode Scanner Optional, Honeywell N3680 hard decode Optical resolution: 5mil Scanning speed: 30 times /s Support code: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverses, Han Xin, Han Xin Inverse NFC 13.56MHz, Support ISO/IEC 14443A/14443B/15693/18092/mifare protocol, reading distance: 3-5cm

*Specification is subject to change without prior notice



Fast charge adapter
and CtoC data cable




Hand-strap



Docking charger DC61J
(Optional)



Vehicle Mount
(Optional)



TP Resist film
(Optional)

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

