









NLS-MT90

PORTABLE DATA COLLECTOR

FEATURES

O Rugged Construction

The NLS-MT90's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.5m drops to concrete.

O Customized Android

The value-added features of the NLS-MT90, including application protection and admin tool, seek to shore up Android's data security.

Long Battery Life

The NLS-MT90 is equipped with a 4500mAh battery that provides a full-shift battery life of up to 10 hours from a single charge. What's more, the battery is changeable which guarantees the all-day continue use of device.

O Diverse Functionalities

The NLS-MT90 offers 1D/2D/BT/Wi-Fi /GPS/Camera/NFC functionalities to meet various application needs.















2D Barcode

1D Barcode

1.5m Dror

IP6F

WiFi

NLS-MT9055(WiFi)

Performance

Processor 2.0GHz, octa-core 64-bit processor

Operating System Android 11

Memory 4GB RAM, 64GB ROM

Interface USB 2.0 OTG at the bottom, 8Pin extended contact on the back

Physical/Electrical

Dimensions (L×W×H) Maximum Size: 155 × 78 × 20mm;

Handheld Size: 155 × 76 × 18mm

Weight 270g (including battery)

5" (1280×720) capacitive touch screen Display

10 keys (side keys included) Keypad

Notification Vibrator, speaker and multi-color LEDs

3.8V, 4500mAh Battery

Camera Front camera (optional): 2 megapixels

Rear camera: 8 megapixels, auto focus, with LED flashlight

GPS GPS (AGPS)/GLONASS/Beidou

Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz AC Adapter

Environmental

Operating Temperature -20°C to 55°C (-4°F to 131°F) -40°C to 70°C (-40°F to 158°F) Storage Temperature

Humidity 5% to 95% (non-condensing)

Static Discharge ±15 kV (Air discharge), ±8 kV (Direct discharge)

1.5m drops to concrete (for six sides, one drop per side) Drop

Tumble Spec. 0.5m, 10 times/min, 500 times(250 tumbles)

Sealing IP65 or IP67 (optional)

Barcode Scanning

1D: Code128, Code 49, Code 16K, (GS1128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC-2D Barcode CMOS (≥5mil)

A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, Codabar,

Code93, Code 11, Plessey, MSI Plessey, RSS.

2D: Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data

Depth of Field

Depends on barcode type and environment QR (15mil) 55mm-410mm; EAN 13 (13mil) 70mm-610mm

Code 39 (5mil) 110mm-290mm; DM (10mil) 110mm-260mm

PDF 417 (6.7mil) 110mm-230mm;

NFC

ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693 13.56MHz RFID

Newland AIDC

Add: No.1 Rujiana West Rd., Mawei, Fuzhou, Fujian 350001, China Tel: +86-591-83979500 Fax: +86-591-83979216 Email: info@newlandaidc.com

Web: www.newlandaidc.com

Newland Aisa Pacific

Add: 6 Raffles Quay #14-06 Singapore 048582 Email: info@newlandaidc.com Japan

電話: +81 03 4405 3222

Tel: +82 10 8990 4838

Taiwan

Tel: +886 2 7731 5388

Indonesia

Tel: +62 8161157247 Vietnam

Tel: +84 909 345 375 India

Tel: +91 120 7964266



NLS-MT9055(WiFi)

Wireless

WLAN RADIO Bands Built-in 802.11 a/b/g/n/ac, Support 2.4G and 5G dual frequency

Bluetooth 5.0 (backward-compatible) WPAN RADIO

Accessory (Optional)

AC adapter, cable, battery, charging cradle, wrist lanyard, trigger handle, RFID handheld reader, long-range barcode reader, protective case, etc.

Specifications are subject to change without notice.

Newland AIDC

Add: No.1 Rujiang West Rd., Mawei, Fuzhou, Fujian 350001, China Tel: +86-591-83979500 Fax: +86-591-83979216 Email: info@newlandaidc.com

Web: www.newlandaidc.com

Newland Aisa Pacific

Add: 6 Raffles Quay #14-06 Singapore 048582 Email: info@newlandaidc.com Japan

電話: +81 03 4405 3222

Tel: +82 10 8990 4838

Taiwan

Tel: +886 2 7731 5388

Indonesia

Tel: +62 8161157247 Vietnam

Tel: +84 909 345 375

Tel: +91120 7964266

