

XB-6221 2D Barcode Scanner Wired Handheld Barcode Scanner Support Data Matrix QR PDF417 Codes

About Specification

Performance Parameters	
Light Sources:	617nm LED Aimer, White LED
Supported Symbologies:	1D: Codabar, Code 11, Code 93, EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Interleave 2 of 5, Matrix 2 of 5, MSI Code, Industrial 2 of 5, GS1-DataBar. 2D: QR Code, Data Matrix, PDF417.
Scan Type:	Image CMOS
Precision:	≥5mil
Scan Mode:	Manual/Continuous/Automatic Scintillation
Scan Angle:	Yaw65°, Rotaion 30°, Pitch60°
Depth of scan field:	60-250mm
Error Rate:	Less than 1/5million
Interfaces:	USB HID/USB-COM/RS-232
Physical Parameters	
Dimensions:	79.7mm*69mm*187mm
Weight:	113.4g
Housing Material:	PC+ABS
Cable Length:	2M
Environmental Parameters	
Operating Temperature:	-20°C ~ 60°C
Storage Temperature:	-40°C ~ 70°C
Relative Humidity:	5%~95% RH(non-condensing/non-freezing)
Shock Resistance:	Withstands multiple times 1.5 meters drops to concrete
Electrical Parameters	
Voltage:	DC5V±5%
Operating Currents:	135mA

